

Cytological Centrifuge

Basic cell sampling centrifuge.

Cellspin

3,000 MAX. RPM	1,057 MAX. RCF	0.5~6ml X 12 MAX. CAP
--------------------------	--------------------------	------------------------------------



Features

- Easy to remove rotor for convenient washing
- Polycarbonate window allows the operator to see the sealed head during cyto-centrifugation
- Auto-locking, plastic outer lid
- No rotor cover requiring sterilization

Max. RPM	3,000rpm
Max. RCF	1,057 x g
Max.capacity	12 slide x 0.5-6ml
Timer	99min
Brake selection	Slow, Normal, Fast (3 step)
Programmability	10 memory
Digital display	RPM, Time, Brake, Program
Drive motor	High torque DC motor
Power supply	AC110/220V, 50/60Hz, Single Phase / 0.6Kw
Dimension	360W x 410D x 280H/mm
Specimen range	0.5 to 6ml
Weight	24Kg

* Please note that technical specifications subject to change.

Basic multipurpose centrifuge for laboratories in hospitals and universities.

HA 12

3,600 MAX. RPM	1,811 MAX. RCF	15ml X 6 MAX. CAP
--------------------------	--------------------------	--------------------------------



Max. RPM	3,600rpm
Max. RCF	1,811 x g
Max. capacity	6 x 15ml
Drive motor	High torque DC motor
Power supply	AC110/220V, 50/60Hz, Single Phase / 0.3kw
Rotor	Angle
Radius	12.5cm
Weight	10Kg

* Please note that technical specifications subject to change.